



More Info

Data sheet



thermoport[®] canteen (hybrid 140°C)

The complete mobile canteen - for transport and serving.

The mobile frontloader, with a hybrid door (140°C) as standard, is suitable for mobile and fully functional regeneration/preparation and can be moved flexibly to any serving situation and quickly configured as a complete serving canteen on site. With a choice of programs for keeping food cold and hot at the same time or separately, as well as for regenerating and cooking food. The food in the interior of the trolley is safely transported and kept hot and can be served directly from the inserted GN containers via the removable lid on top and from the hinged GN mounting frames on the sides. Quick replenishment of food from the interior. Can be flexibly expanded with other mobile Rieber system products, such as serving trolleys.

The hybrid door (140°C) can be replaced with an active functional door in seconds. The door with circulating air heating is suitable for actively keeping food hot. An additional cooling option is possible with all door options through the insertion of GN 1/1 cooling pellets. The neutral door is suitable for the transport of food and for keeping the food hot. Another optional accessory is the hinged and lockable germ guard screen on the guest side. All Rieber thermoport[®] made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys. Configuration with GN containers and GN thermoplates[®] in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid[®] lid for low-temperature cooking.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

thermoport® canteen (hybrid 140°C)



TECHNICAL SPECIFICATIONS

Dimensions	592 x 788 x 959 mm
Material	stainless steel 1.4301 (CNS)
Weight	56,8 kg
Connected load	3.300 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	1.500 mm
Heating Area	max. +140°C
Capacity with GN	70 L
Protection class	IPX5
Support rails	16
Rail distance	37 mm
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Castor type	Rustproof
Wheel diameter	125 mm
GN-Norm	GN 1/1

Order number 85 01 09 19

BENEFITS

2x 1/1 GN mounting frames on the right and 1x GN 1/1 on the left, can be securely hinged and locked in a 90° horizontal serving position.

Double-walled insulation, low loss of heat/cold and uniform heat distribution, even when fully loaded.

With a controllable steam function.

Door with a door lock on the serving side for safe and easy one-handed operation.

Mobile with robust, fixable castors and a push handle.

Door with a steam safety device (2-stage) on the serving side for safe and easy one-handed operation.

Mobile with robust, fixable castors and a push handle.

Removable door seal/heating system, quick and easy cleaning.

High-pressure cleaner can be used on the interior with the door removed, splash-proof (IPX5).